

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012)

Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture

Product name : Plink Garbage Disposal Freshener & Cleaner - Simply Fresh

1.2. Recommended use and restrictions on use

Recommended use : Freshener

1.3. Supplier

Iron Out dba Summit Brands 6714 Pointe Inverness Way, Suite 200 Fort Wayne, IN 46804-7935 LIS

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA/US)

Flammable liquids Category 3 Skin corrosion/irritation Category 2 Skin sensitization, Category 1

Not classified

Flammable liquid and vapor Causes skin irritation

May cause an allergic skin reaction

2.2. GHS Label elements, including precautionary statements

GHS CA/US labeling

Hazard pictograms (GHS CA/US)





Signal word (GHS CA/US) : Warning

Hazard statements (GHS CA/US) : Flammable liquid and vapor

Causes skin irritation

May cause an allergic skin reaction

Precautionary statements (GHS CA/US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical, ventilating, lighting equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Avoid breathing mist, vapors.

Wash hands, forearms and face thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection, face protection.

In case of fire: Use media other than water to extinguish.

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

> IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Specific treatment (see supplemental first aid instruction on this label).

If skin irritation or rash occurs: Get medical advice or attention.

Store in a well-ventilated place. Keep cool

Dispose of container in accordance with local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA/US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
D-Limonene	CAS-No.: 5989-27-5	65 - 85
1,2,3-Propanetriol	CAS-No.: 56-81-5	7 – 10
Paraffin waxes and Hydrocarbon waxes	CAS-No.: 8002-74-2	5 - 10

Comments

: All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Obtain medical attention if irritation persists. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice or

attention. If skin irritation or rash occurs: Get medical help.

First-aid measures after eye contact Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation persists.

Do not induce vomiting. If vomiting occurs have person lean forward. Never give anything by

First-aid measures after ingestion mouth to an unconscious person. Call a poison center or a doctor if you feel unwell. First-aid measures general

If you feel unwell, seek medical advice (show the label where possible). Medical personnel should be made aware of substance(s) involved and take measures for self protection. Show this safety data sheet to the doctor in attendance. Avoid contact with skin and eyes. Keep out of the reach of children.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Prolonged inhalation may be harmful.

8/30/2024 (Revision date) CA/US 2/12

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

Symptoms/effects after skin contact : Prolonged or repeated contact may dry skin and cause irritation. Causes skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause

an allergic skin reaction.

Symptoms/effects after eye contact : Direct contact with eyes may cause temporary irritation.

Symptoms/effects after ingestion : May cause stomach distress, nausea or vomiting.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Symptoms may be delayed. Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Treat for surrounding material.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Flammable liquid and vapor. During fire, gases hazardous to health may be formed. In case of

fire or explosion do not breathe fumes.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : May include and are not limited to: oxides of carbon.

5.4. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Keep unnecessary personnel away. For personal protection, see section 8 of the SDS. In the event of a significant spillage : Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leaks if it can be done without personal risk. Contain any spills with dikes or absorbents to

prevent migration and entry into sewers or streams.

Methods for cleaning up : Notify authorities if product enters sewers or public waters. Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel). Take up mechanically (sweeping,

shoveling) and collect in suitable container for disposal. Clean contaminated surfaces with an

excess of water. Minimize generation of dust.

Other information : This material and its container must be disposed of in a safe way, and as per local legislation.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

8/30/2024 (Revision date) CA/US 3/12

Safety Data Sheet

Hygiene measures

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not taste or swallow.

Ensure good ventilation of the work station. Handle and open container with care.

: Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Take off contaminated clothing and wash it before reuse. Contaminated work clothing

should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep out of reach of

children. Store tightly closed in a dry, cool and well-ventilated place. Store away from

incompatible materials (see Section 10 of the SDS).

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

D-Limonene (5989-27-5)		
USA - AIHA - Occupational Exposure Limits		
WEEL TWA	30 ppm	
1,2,3-Propanetriol (56-81-5)		
Canada (Alberta) - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
Notations and remarks	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.	
Regulatory reference	Alberta Regulation 191/2021	
Canada (Quebec) - Occupational Exposure Limits		
VEMP (OEL TWAEV)	10 mg/m³	
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety	
Canada (British Columbia) - Occupational Exposure Limits		
OEL TWA	10 mg/m³ Total 3 mg/m³ Respirable	
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)	
Canada (New Brunswick) - Occupational Exposure Limits		
Notations and remarks	URT irr	
Canada (Nunavut) - Occupational Exposure Limits		
OEL TWA	10 mg/m³	
OEL STEL	20 mg/m³	
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)	

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

1,2,3-Propanetriol (56-81-5)	1,2,3-Propanetriol (56-81-5)		
Canada (Northwest Territories) - Occupational Expo	osure Limits		
OEL TWA	10 mg/m³		
OEL STEL	20 mg/m³		
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)		
Canada (Ontario) - Occupational Exposure Limits			
OEL TWAEV	10 mg/m ³		
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833		
Canada (Saskatchewan) - Occupational Exposure L	imits		
OEL TWA	10 mg/m ³		
OEL STEL	20 mg/m³		
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10		
Canada (Yukon) - Occupational Exposure Limits			
OEL TWA	30 mppcf (mist) 10 mg/m³ (mist)		
USA - OSHA - Occupational Exposure Limits			
OSHA PEL TWA	15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
Paraffin waxes and Hydrocarbon waxes (8002-74-2)			
Canada (Alberta) - Occupational Exposure Limits			
OEL TWA	2 mg/m³ (fume)		
Regulatory reference	Alberta Regulation 191/2021		
Canada (Quebec) - Occupational Exposure Limits			
VEMP (OEL TWAEV)	2 mg/m³ (fume)		
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety		
Canada (British Columbia) - Occupational Exposure	e Limits		
OEL TWA	2 mg/m³ (fume)		
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)		
Canada (Manitoba) - Occupational Exposure Limits	Canada (Manitoba) - Occupational Exposure Limits		
OEL TWA	2 mg/m³ (fume)		
Notations and remarks	TLV® Basis: URT irr; nausea		
Regulatory reference	ACGIH 2024		
Canada (New Brunswick) - Occupational Exposure Limits			
OEL TWA	2 mg/m³ (fume)		
Notations and remarks	URT irr; nausea		
Canada (Newfoundland and Labrador) - Occupation	nal Exposure Limits		
OEL TWA	2 mg/m³ (fume)		

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

Paraffin waxes and Hydrocarbon waxes (8002-74-2)			
Notations and remarks	TLV® Basis: URT irr; nausea		
Regulatory reference	ACGIH 2024		
Canada (Nova Scotia) - Occupational Exposure Limits			
OEL TWA	2 mg/m³ (fume)		
Notations and remarks	TLV® Basis: URT irr; nausea		
Regulatory reference	ACGIH 2024		
Canada (Nunavut) - Occupational Exposure Limits			
OEL TWA	2 mg/m³		
OEL STEL	4 mg/m³		
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)		
Canada (Northwest Territories) - Occupational Expo	osure Limits		
OEL TWA	2 mg/m³		
OEL STEL	4 mg/m³		
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)		
Canada (Ontario) - Occupational Exposure Limits			
OEL TWAEV	2 mg/m³ (fume)		
Regulatory reference	Ontario Occuational Exposure Limits under Regulation 833		
Canada (Prince Edward Island) - Occupational Exposure Limits			
OEL TWA	2 mg/m³ (fume)		
Notations and remarks	TLV® Basis: URT irr; nausea		
Regulatory reference	ACGIH 2024		
Canada (Saskatchewan) - Occupational Exposure L	imits		
OEL TWA	2 mg/m³		
OEL STEL	4 mg/m³		
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10		
Canada (Yukon) - Occupational Exposure Limits	Canada (Yukon) - Occupational Exposure Limits		
OEL TWA	2 mg/m³ (fume)		
OEL STEL	6 mg/m³ (fume)		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	2 mg/m³ (fume)		
Remark (ACGIH)	TLV® Basis: URT irr; nausea		
Regulatory reference	ACGIH 2024		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL TWA	2 mg/m³ (fume)		

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

8.2. Appropriate engineering controls

Appropriate engineering controls : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates

should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear protective gloves. Confirm with a reputable supplier first. Wear suitable gloves resistant to chemical penetration

Eye protection:

Wear eye protection

Skin and body protection:

Wear suitable protective clothing. As required by employer code.

Respiratory protection:

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Solid bead containing liquid inside.

Color slightly hazy Green Odor Citrus Orange Odor threshold No data available No data available Ηα Relative evaporation rate (butyl acetate=1) No data available Relative evaporation rate (ether=1) No data available Melting point No data available Freezing point Not applicable Boiling point No data available

Flash point : 129.2 °F (54.0 °C) ASTM D3828 (Liquid inside bead)

Auto-ignition temperature : Not applicable Decomposition temperature : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20°C No data available Relative density No data available Solubility No data available Partition coefficient n-octanol/water (Log Pow) No data available Viscosity, kinematic Not applicable Explosive properties Not explosive. Oxidizing properties Not oxidising. Not applicable **Explosion limits**

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity : Flammable liquid and vapor.
Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

Incompatible materials : Strong oxidizing agents.

Hazardous decomposition products : May include and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) :

D-Limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 5 g/kg (Source: CHEMVIEW)
LC50 Inhalation - Rat (Vapours)	> 20 mg/l/4h
ATE CA (oral)	4400 mg/kg body weight

1,2,3-Propanetriol (56-81-5)	
LD50 oral rat	12600 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 10 g/kg (Source: NLM_CIP)
LD50 dermal	56750 mg/kg (4 day(s), Guinea pig, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 2.75 mg/l/4h
LC50 Inhalation - Rat (Vapours)	5.85 mg/l/4h
ATE CA (oral)	12600 mg/kg body weight
ATE CA (Dermal)	56750 mg/kg body weight
ATE CA (vapors)	5.85 mg/l/4h

Paraffin waxes and Hydrocarbon waxes (8002-74-2)	
LD50 oral rat	> 5000 mg/kg (Source: CHEMVIEW)
LD50 dermal rabbit	> 3600 mg/kg (Source: NLM_CIP)

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

D-Limonene (5989-27-5)	
IARC group	3 - Not classifiable
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity
Reproductive toxicity	Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Likely routes of exposure	: Skin and eye contact. Ingestion. Inhalation.
Symptoms/effects after inhalation	: Prolonged inhalation may be harmful.
Symptoms/effects after skin contact	Prolonged or repeated contact may dry skin and cause irritation. Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Direct contact with eyes may cause temporary irritation.
Symptoms/effects after ingestion	: May cause stomach distress, nausea or vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : See below for route-specific details.

Unknown hazards to the aquatic environment (GHS : Contains 0.02 % of components with unknown hazards to the aquatic environment

CA)

Hazardous to the aquatic environment, short-term : Not classified.

(acute)

Hazardous to the aquatic environment, long-term : Not classified.

(chronic)

D-Limonene (5989-27-5)	
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: EPA)
EC50 - Crustacea [1]	0.307 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	0.51 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	0.32 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.214 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

1,2,3-Propanetriol (56-81-5)	
LC50 - Fish [1]	51 – 57 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
	> 10000 mg/l (24 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)

12.2. Persistence and degradability

1,2,3-Propanetriol (56-81-5)	
Persistence and degradability	Readily biodegradable in water.

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

12.3. Bioaccumulative potential

D-Limonene (5989-27-5)	
Partition coefficient n-octanol/water (Log Pow)	4.38 (at 37 °C (at pH 7.2)

1,2,3-Propanetriol (56-81-5)	
Bioaccumulative potential	Not bioaccumulative.
BCF - Fish [1]	(no bioaccumulation)
Partition coefficient n-octanol/water (Log Pow)	-1.75 (at 25 °C (at pH 7.4)

12.4. Mobility in soil

1,2,3-Propanetriol (56-81-5)		
Surface tension	63 mN/m (20 °C, 1000 g/l)	
Ecology - soil	Highly mobile in soil.	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0 (log Koc, SRC PCKOCWIN v2.0, Calculated value)	

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

- : Dispose of the material collected according to regulations.
- : Disposal must be done according to official regulations.
- : Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling, disposal or collection. Dispose of contents/container to hazardous or special waste collection

point, in accordance with local, regional, national and/or international regulation.

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

General information: This product is a gel bead which contains a flammable liquid within; DOT - 49 CFR 173.150 (f) - Combustible Liquid Exemption

Constant the product of a gold sound than the state of th			
TDG	DOT		
14.1. UN number			
UN1993	UN1993		
14.2. Proper Shipping Name			
FLAMMABLE LIQUID, N.O.S. (D-Limonene)	Flammable liquids, n.o.s. (D-Limonene)		
Transport document description			
UN1993 FLAMMABLE LIQUID, N.O.S. (D-Limonene), 3, III	UN1993 Flammable liquids, n.o.s. (D-Limonene), 3, III		
14.3. Transport hazard class(es)			
3 (LTD QTY)	3 (LTD QTY)		

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

TDG	DOT	
3	FLAMMABLE LIQUID	
14.4. Packing group		
III	III	
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No	
No supplementary information available		

14.6. Special precautions for user

TDG

UN-No. (TDG) : UN1993 Excepted quantities (TDG) : E1 Emergency Response Guide (ERG) Number : 128

DOT

UN-No.(DOT) : UN1993

DOT Special Provisions (49 CFR 172.102)

B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail (49 : 60 L

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75)

: 220 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Safety Data Sheet

according to the Hazardous Products Regulation (WHMIS 2015) & OSHA Hazard Communication Standard 29 CFR 1910.1200 (HazCom 2012) Issue date: 8/30/2024 Revision date: 8/30/2024 Version: 04.0

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are present on DSL.

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

 Issue date
 : 08/30/2024

 Revision date
 : 08/30/2024

Other information : For an updated SDS, please contact the supplier or manufacturer listed on the first page of the

document. Redbook revision #7, 5/1/18.

The information in the safety data sheet was written by Dell Tech Laboratories Ltd. (www.delltech.com) based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.